



C07 CATALIZZATORE LIQUIDO

Liquid catalyst

A) DESCRIPTION AND FIELDS OF APPLICATION:

For M27 and M25 Epoxy glues.

B) TECHNICAL DATA:

Composition	Aliphatic polyamine
Specific weight	1±0,1
Available colours	Clear straw
Safety data	See safety data sheet

C) PROCESSING :

Mixing ratio: With M27
: 8% by weight or 12:1 by volume, that is 12 parts of M27 glue and one part of C07 catalyst.
With M25 : 20% by weight or 5:1 by volume, that is 5 parts of M25 glue and one part of C07 catalyst.

D) CAUTIONS:

- * Mistakes higher than 10% more or less on the catalyst ratio may compromise the final characteristics of the product.
- * Keep containers well closed. Be sure that all working instruments and mixing tanks are perfectly dry.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A

42100 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42100 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42100 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42025 Cavriago - Via Nizzola, 5 - Tel. +39 0522 371818 - Fax +39 0522 575110

Stabilimento: 06074 Perugia - Via Trasimeno Ovest, 159/Z/13 - Tel. +39 075 518611 - Fax +39 075 5186125

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357