



# H65 2K UHS CLEARCOAT

## Ultra high solids acrylic clear coat

### A) DESCRIPTION AND FIELDS OF APPLICATION:

Two-component, acrylic ultra high solid clear coat complying with VOC standard limits. Its main features include its high dry residue offering better yield, its excellent spreading and gloss, its fast drying and particularly intense finish achieved.

The EU limit for this product (product category IIB.d) is 420 g/l. The VOC of this product is 420g/l.

### B) TECHNICAL DATA:

Composition	Hydroxylated acrylic resins
Specific weight	0,98 ± 0,03
Available colours	Neutral clear
Safety data	Refer to the safety sheet

### C) SURFACE PREPARATION :



\* Matt base coat for two coats of solvent-based paint

\* Matt base coat for two coats of water-based paint

### D) CAUTIONS:

- \* 2k acrylic paints are affected by moisture.
- \* Comply with the dilution stated.
- \* Do not use the product at temperatures below 5°C.
- \* Keep in a cool, dry place.

**E) PROCESSING:****3:1 C65/C66 UHS Hardener potlife > 60' at 20°C.****19-20" CF 4 at 20°C.****1,3-1,4 mm 3,5-4 bar  
1+1/2 = 60-70 micron****1,4-1,5 mm 3,5-5 bar  
1+1/2 = 60-70 micron****10'-15' drying depending on temperature****8 h at 20°C.  
30' at 60°C.****12' at 1 mt.****F) TOOLS CLEANING:**

With thinner for polyurethane products.

**G) RECOATING :**

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained