


Safety Data Sheet

H66 2K UHS PRESTIGE



Safety Data Sheet dated 31/10/2007, version 1

1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

Trade name: H66 2K UHS Prestige

Trade code: H66

Product type and use: Bi-component acrylic clearcoat

Company:

Ind. Chimica Reggiana spa Via Gasparini, 7 42100 Reggio Emilia ITALY

Tel. +39 0522-517803 Fax +39 0522-514384

Safety data office:

sdsre@icrsprint.it

Emergency telephone number of the company and/or of an authorised advisory centre:

Industria Chimica Reggiana - Tel. +39-0522-514803

2. HAZARDS IDENTIFICATION

The product is a liquid that can catch fire at temperatures in excess of 21 °C if exposed to an ignition source.

If brought into contact with the eyes, the product causes irritation that may last for over 24 hours, and if brought into contact with the skin it causes significant inflammation with erythema, scabs, and oedema.

Repeated exposure to the product may cause skin dryness or cracking.

Vapours of the product may cause drowsiness and dizziness.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components within the meaning of EEC directive 67/548 and corresponding classification:

20% - 25% *n*-butyl acetate

N.67/548/CEE: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1

R10-66-67; substance with a Community workplace exposure limit

7% - 10% Solvent naphtha (petroleum), light aromatic

N.67/548/CEE: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0

Xn,Xi,N; R10-37-51-53-65 Note P

7% - 10% 2-butoxyethyl acetate

N.67/548/CEE: 607-038-00-2 CAS: 112-07-2 EC: 203-933-3

Xn; R20/21

5% - 7% Xylene

N.67/548/CEE: 601-022-01-6 CAS: 1330-20-7 EC: 215-535-7

Xn,Xi; R10-20/21-38

3% - 5% 4-methylpentan-2-one

N.67/548/CEE: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1

F,Xn,Xi; R11-20-36/37-66

1% - 3% Dimethyl dodecyl amine, distilled

CAS: 112-18-5 EC: 203-943-8

Xn,C,N; R50-34-22

1% - 3% Acetone

N.67/548/CEE: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2

F,Xi; R11-36-66-67



Safety Data Sheet

H66 2K UHS PRESTIGE

0.25% - 0.5% Reaction products of 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy)methyl)oxyrane
N.67/548/CEE: 603-155-00-8 EC: 410-560-1
N; R50-53

0.25% - 0.5% Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
CAS: 41556-26-7 EC: 255-437-1
Xi,N; R43-50-53

4. FIRST AID MEASURES

Contact with skin:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Contact with eyes:

Wash immediately with water for at least 10 minutes.

Swallowing:

Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

A suspension of activated charcoal in water, or liquid paraffin may be administered.

Inhalation:

Ventilate the premises. The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area. Should the patient feel unwell, OBTAIN MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES

Recommended extinguishers:

CO₂ or dry chemical fire extinguishers.

Extinguishers not to be used:

None in particular.

Risks arising from combustion:

Avoid inhaling the fumes.

Protective equipment:

Use protection for the respiratory tract.

Cool the containers exposed to the fire with water.

6. ACCIDENTAL RELEASE MEASURES

Measures for personal safety:

Use a mask, gloves and protective clothing.

Environmental measures:

Limit leakages with earth or sand.

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

Cleaning methods:

Rapidly recover the product. To do so, wear a mask and protective clothing.

If the product is in a liquid form, stop it from entering the drainage system.

Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.

7. HANDLING AND STORAGE

Handling precautions:

Avoid contact and inhalation of the vapours. See, too, paragraph 8 below.

Do not eat or drink while working.

Do not smoke while working.

Incompatible materials:

None in particular.



Safety Data Sheet

H66 2K UHS PRESTIGE

Storage conditions:

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment, e.g. CEN/FFP-2(S) or CEN/FFP-3(S).

Protection for hands:

Use protective gloves that provides comprehensive protection, EN374 Class 3. E.g. neoprene or nitrile

Eye protection:

Not needed for normal use, however adopt good working practices.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Exposure limit(s) (ACGIH):

Name	TLV - TWA	TLV - STEL
<i>n</i> -butyl acetate	100 ppm	150 ppm
Xylene	100 ppm	150 ppm
4-methylpentan-2-one	50 ppm	75 ppm, 307mg/m ³
Acetone	1000 ppm	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: Transparent colourless liquid

Odour: Typical of solvent

Flash point: > 21 °C.

Relative density: 0,98

10. STABILITY AND REACTIVITY

Conditions to avoid:

Stable under normal conditions.

Substances to avoid:

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products:

None.

11. TOXICOLOGICAL INFORMATION

The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Set out below is the toxicological information relating to the main substances in the preparation.

n-butyl acetate

OBSERVATIONS ON HUMAN SUBJECTS:

Inhalation: 3300 ppm (16 mg/l), for short periods, cause serious irritation to the eyes and to the nose.

Inhalation: 200-300 ppm (1-1.4 mg/l), for short periods, cause moderate irritation to the eyes and to the nose.

Inhaling the vapours can irritate the respiratory system.

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2,000 ppm for 60 min.

TCLo: 200 ppm



Safety Data Sheet

H66 2K UHS PRESTIGE

Solvent naphtha (petroleum), light aromatic

Acute toxicity:

Inhalation: vapour concentrations exceeding recommended exposure levels are irritating to eyes and respiratory tract, and may cause headache, dizziness and other effects on the central nervous system.

Skin contact: Low toxicity index.

Frequent or prolonged contact may dry the skin, causing dermatitis.

Eye contact: may cause discomfort to eyes with slight irritation, but with no tissue damage.

Ingestion: even small amounts of liquid introduced into the respiratory system during ingestion may cause bronchitis or lung damage. Low toxicity index.

2-butoxyethyl acetate

Ways of penetrating: by swallowing, inhalation, contact.

Acute toxicity: a large amount when swallowed can cause gastroenteric irritation, strong depression of the central nervous system, hematic effects and lesions to the liver and kidneys. Can seriously damage the lungs if aspirated when swallowing or vomiting.

Inhalation: Serious irritation of the eyes and respiratory tracts following lengthy exposure.

Contact: the product is easily absorbed. Repeated and prolonged contact can cause irritation and dermatitis.

Eyes: contact with the eyes is painful, causing irritation of the conjunctiva and lesions to the cornea.

Xylene

OBSERVATIONS ON HUMAN SUBJECTS NON-PROFESSIONAL EXPOSURE - Effects following acute exposure:

Symptoms of intense exposure are: dermatitis, eczema, irritation to the eyes and to the respiratory tract.

Inhaling the vapours can cause dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

PROFESSIONAL EXPOSURE - Effects following acute exposure:

Narcotic at high concentrations.

Irritation through inhalation at 200 ppm (TCLo). Inhalation of 200 ppm has irritating effects in human subjects.

Human subject (oral)(LDLo): 50 mg/kg.

Inhalatory human subject (LCLo) 10000 ppm/6h.

4-methylpentan-2-one

Ways of penetrating: by inhalation, through the skin, by digestion.

Acute toxicity:

Irritation of the eyes: weakly irritating.

Irritation of the skin: weakly irritating.

Irritation of the respiratory tracts: weakly irritating.

Effects on man: high exposure can cause drowsiness and vertigo. Prolonged and repeated contact can cause dermatitis. Contact with the eyes is painful.

Effects on other organs and apparatus: narcosis and depression of the central nervous system, vomiting, diarrhea, damage to the liver and kidneys.

Acetone

OBSERVATIONS IN MAN:

Acetone can penetrate into the organism through cutaneous absorption, swallowing, but above all through inhalation. It is eliminated via the lungs (40-70%), urine (15-30%) and through the skin (10%). Research conducted with C14 has shown that acetone enters as intermediate into the metabolism of lipids and indirectly into the cycle of glycolides. Tests on man have shown that it is impossible to inhale concentrations of 22 mg/l (9300 ppm) for more than 5 minutes owing to irritation of the throat. Persons exposed to 500 ppm of acetone have shown irritation of the eyes, throat and nose.

Concentrations > 300 ppm cause slight irritation of the mucous membranes.

Concentrations = 4000 ppm (60 min) cause serious toxic effects.

Concentrations = 800 ppm (30 min) cause discomfort.

DL (estimated oral) = 50 ml.

Safety Data Sheet

H66 2K UHS PRESTIGE

12. ECOLOGICAL INFORMATION

Adopt good working practices, so that the product is not released into the environment.

List of substances dangerous for the environment and corresponding classification:

7% - 10% solvent naphtha (petroleum), light aromatic

N.67/548/CEE: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Mobility: floats on water; evaporates from water and land surface but if significant part may penetrate and pollute ground water.

Persistence / degradability: assume the product is not rapidly biodegradable (from data of the component substances).

Bio-accumulation: product may be potentially bio-accumulative.

Ecotoxicity: assume product is toxic to aquatic organisms.

1% - 3% Dimethyl dodecyl amine, distilled

CAS: 112-18-5 EC: 203-943-8

R50 Very toxic to aquatic organisms.

0.25% - 0.5% Reaction products of 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy)methyl)oxyrane

N.67/548/CEE: 603-155-00-8 EC: 410-560-1

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

0.25% - 0.5% Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

CAS: 41556-26-7 EC: 255-437-1

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

The waste of non-polymerized material must be considered as "Toxic and Harmful" waste, due to the presence of organic solvents higher than that permitted by European laws.

The empty containers must be considered as Special Waste Materials and disposed of at Type 2B Waste Dumps. If previously cleansed, they can be admitted in first class dumps.

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

Limited quantities, not liable to ADR norms for internal packages of up to 5L and a maximum 30 kg per pack.

UN number:	1263
Packing Group:	III
Shipping Name:	Paint
Transport category :	3
ADRRID-Class:	3
Classification code :	F1
Label:	3
IMDG-Class:	3
IMDG-Label:	3
IMDG-EMS:	F-E, S-E

Marine pollutant MARPOL (Annex II/III) : Yes



Safety Data Sheet

H66 2K UHS PRESTIGE

15. REGULATORY INFORMATION

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments.

Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments.

Commission Directive 98/24/EC (Protection of the health and safety of workers from the risk related to chemical agent).

Commission Directive 2000/39/EC (Occupational exposure limit values).

Regulation (EC) No 1907/2006 (REACH).

Symbols:

Xi Irritant

R Phrases:

R10 Flammable.

R36/38 Irritating to eyes and skin.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S Phrases:

S23 Do not breathe spray.

S37 Wear suitable gloves.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Contains:

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate: May produce an allergic reaction.

Volatile Organic Compounds - VOCs = 470 g/L

Volatile CMR substances = 0,00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0,00 %

Organic Carbon - C = 0,22

VOC with hardener (ready to use) = 417 g/L

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

16. OTHER INFORMATION

Text of R phrases referred to under heading 3:

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R22 Harmful if swallowed.

R34 Causes burns.

R36 Irritating to eyes.

R36/37 Irritating to eyes and respiratory system.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R50 Very toxic to aquatic organisms.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Safety Data Sheet

H66 2K UHS PRESTIGE

R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

ACGIH - Threshold Limit Values - 2004 edition

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

