

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY



Safety Data Sheet dated 2/12/2021, version 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Mixture identification:
Trade code and name: F31 PLUS FILLER HS DARK GREY
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Two-component primer-surfacer for autobody use
Only for professional use.
- 1.3. Details of the supplier of the safety data sheet
Company:
Industria Chimica Reggiana I.C.R. Spa
(subject to management and coordination by sole shareholder company PPG Industries Inc.)
Via Gasparini, 7 42124 REGGIO EMILIA Italia
Tel. +39 0522/517803 Fax +39 0522/514384
Competent person responsible for the safety data sheet:
sdsre@icrsprint.it
- 1.4. Emergency telephone number
Tel. +39 0522-517803 or NHS 111 - dial 111

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)
- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
 - ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
 - ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H317 May cause an allergic skin reaction.

Precautionary statements:

- P210 Keep away from open flames - No smoking..
- P260 Do not breathe vapours or spray.
- P280.D Wear protective gloves and clothing and eye protection.
- P312 Call a doctor if you feel unwell.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

maleic anhydride

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Fatty acids, C14-18 and C16-18-unsatd., maleated
 Special provisions according to Annex XVII of REACH and subsequent amendments:
 None

2.3. Other hazards
 vPvB Substances: None - PBT Substances: None
 Other Hazards:
 No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 10% - < 12.5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336 EUH066
>= 7% - < 10%	Xylene	Index number: 601-022-01-6 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.9/2 STOT RE 2 H373 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H335 4.1/C3 Aquatic Chronic 3 H412
>= 1% - < 3%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336
>= 0.5% - < 1%	Naphtha - hydrocarbons C9 aromatics	CAS: 64742-95-6 EC: 918-668-5 REACH No.: 01-2119455851-35	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.8/3 STOT SE 3 H336 ⚠ 4.1/C2 Aquatic Chronic 2 H411 EUH066
>= 0.1% - < 0.25%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.9/2 STOT RE 2 H373 4.1/C3 Aquatic Chronic 3 H412

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

>= 0.1% - < 0.25%	Fatty acids, C14-18 and C16-18- unsatd., maleated	CAS: 85711-46-2 EC: 288-306-2 REACH No.: 01- 2119976378- 19	⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.4.2/1 Skin Sens. 1 H317
< 0.01%	maleic anhydride	Index number: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 REACH No.: 01- 2119472428- 31	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.9/1 STOT RE 1 H372 ⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.1/1 Resp. Sens. 1 H334 ⚠ 3.4.2/1A Skin Sens. 1A H317 EUH071

This product is not classified H304 due to its high viscosity.

All component substances of this product have been registered under REACH or are exempt from REACH registration.

Substances in Section 3 not showing REACH registration codes are exempt from registration.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. If irritation persists: Get medical advice/attention.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

In case of Inhalation:

Ventilate the premises. The patient is to be removed immediately from the contaminated premises to rest in a well ventilated area. OBTAIN MEDICAL ATTENTION.

4.2. Most important symptoms and effects, both acute and delayed

See section 11 for known symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Do not use water jets. Water may not be effective fire fighting measure, however it can be used to cool closed

containers close to flames as to avoid bursting and exploding.

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Carbon oxides.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

See Point 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate - CAS: 123-86-4

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

Xylene - CAS: 1330-20-7
Italy - TWA(8h): 221 mg/m³, 50 ppm - STEL(): 442 mg/m³, 100 ppm - Notes: Assorbito attraverso la pelle
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
Italy - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: H
EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin

Naphtha - hydrocarbons C9 aromatics - CAS: 64742-95-6
EU - TWA(8h): 100 mg/m³, 19 ppm

ethylbenzene - CAS: 100-41-4
Italy - TWA(8h): 442 mg/m³, 100 ppm - STEL(): 884 mg/m³, 200 ppm - Notes: Pelle
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

maleic anhydride - CAS: 108-31-6
ACGIH - TWA(8h): 0.01 mg/m³ - Notes: (IFV), DSEN, RSEN, A4 - Resp sens

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4
Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 480 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Xylene - CAS: 1330-20-7
Worker Professional: 442 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 212 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Professional: 212 mg/kg - Consumer: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)
Worker Professional: 221 mg/m³ - Consumer: 65.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term (repeated)
Consumer: 12.5 mg/kg/day - Exposure: Human Oral - Frequency: Long Term (repeated)

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
Worker Professional: 153.5 mg/kg - Consumer: 320 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Worker Professional: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 36 mg/kg/day - Exposure: Human Oral - Frequency: Long Term (repeated)
Worker Professional: 550 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 796 mg/kg/day - Consumer: 320 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Naphtha - hydrocarbons C9 aromatics - CAS: 64742-95-6

Worker Professional: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects

Worker Professional: 150 mg/m³ - Consumer: 32 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects

Consumer: 11 mg/m³ - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4

Worker Professional: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term,
local effects

Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects

Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term,
systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: STP - Value: 35.6 mg/l

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Intermittent emissions - Value: 0.36 mg/l

Target: Freshwater sediments - Value: 0.98 mg/kg

Target: Marine water sediments - Value: 0.09 mg/kg

Target: Soil - Value: 0.09 mg/kg

Xylene - CAS: 1330-20-7

Target: Purification plant - Value: 6.58 mg/l

Target: Marine water - Value: 0.32 mg/l

Target: Intermittent emissions - Value: 0.32 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil - Value: 2.31 mg/kg

Target: Fresh Water - Value: 0.32 mg/l

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Intermittent emissions - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg

Target: Marine water sediments - Value: 0.329 mg/kg

Target: Soil - Value: 0.29 mg/kg

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: 14 - Value: 6.35 mg/l

Target: Purification plant - Value: 100 mg/l

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Intermittent emissions - Value: 0.1 mg/l

Target: Freshwater sediments - Value: 13.7 mg/kg

Target: Soil - Value: 2.68 mg/kg

Target: Purification plant - Value: 9.6 mg/l

Target: Oral - Value: 0.02 mg/kg

Biological Exposure Index

Xylene - CAS: 1330-20-7

Value: 1.5 g/g - medium: Urine - Biological Indicator: Creatinine in urine - Sampling Period:
End of turn

ethylbenzene - CAS: 100-41-4

Value: 0.15 g/g - medium: Urine - Biological Indicator: Creatinine in urine - Sampling Period:

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

End of turn

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles and/or visor conforming to BS 2092 GRADE 1).

Protection for skin:

Wear safety clothing that ensure full skin protection in accordance to EN 14605 Type 4 in case of spills or spray (e.g. Tyrek). Please note: safety clothing must be changed immediately if it comes in contact with product.

Protection for hands:

Use protective gloves that provides comprehensive protection, EN374 Class 3 (F-I). Permeation time > 60 minutes; 0.4 mm thickness.

Respiratory protection:

Use adequate protective respiratory devices, using Filter "A" (Brown colour) for organic gas and vapors with boiling points over 65°C.

Thermal Hazards:

None

Environmental exposure controls:

Emissions from ventilation systems or from work processes must be check as to ensure compliance to environmental protection legislation. In some cases the addition of vapour scrubbers, filters or other system modification may be necessary in order to reduce emissions to acceptable levels.

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Grey fluid paste	--	--
Odour:	Typical of solvent	--	--
Odour threshold:	N.D.	--	--
pH:	N.A.		
Melting point / freezing point:	- 54°C	--	--
Initial boiling point and boiling range:	127°C	--	--
Flash point:	23 °C	--	--
Evaporation rate:	N.D.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.D.	--	--

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Vapour pressure:	15 hPa	--	--
Vapour density:	4 (aria = 1)	--	--
Relative density:	1.620 g/cm ³	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.D.	--	--
Partition coefficient (n-octanol/water):		--	--
Auto-ignition temperature:	415°C	--	--
Decomposition temperature:	N.D.	--	--
Viscosity:	> 20,5 mm ² /s (40°C)	--	--
Explosive properties:	N.D.	--	--
Oxidizing properties:	N.D.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under recommended use and storage conditions (see point 7).

10.3. Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), and nitrides.

It may catch fire on contact with oxidising mineral acids, powerful oxidising agents, and powerful reducing agents.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid accumulating electrostatic charge.

Stable under normal conditions.

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 6400 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 21.1 mg/l - Duration: 4h

Xylene - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 6700 ppm - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 5627 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 2000 ppm - Duration: 3h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/l

Naphtha - hydrocarbons C9 aromatics - CAS: 64742-95-6

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m³ - Source: OECD 403

Test: LD50 - Route: Oral - Species: Rat = 3492 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg - Source: OECD 402

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Mouse = 35500 mg/m³

Test: LC50 - Route: Inhalation - Species: Rat = 55000 mg/m³

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Fatty acids, C14-18 and C16-18-unsatd., maleated - CAS: 85711-46-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2.000 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Positive

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: Mouse Positive

maleic anhydride - CAS: 108-31-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1090 mg/kg bw

Test: LD50 - Route: Skin - Species: Rabbit = 2620 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 4.35 mg/l - Duration: 1h

n-butyl acetate - CAS: 123-86-4

Components of the product can be absorbed by the body by inhalation. Main symptoms: Dizziness, narcosis, Cough, nausea, vomiting, headache, unconsciousness, shortness of breath. Repeated exposure can cause skin dryness and cracking.

Xylene - CAS: 1330-20-7

Inhalation: Harmful if inhaled. Very high concentrations of xylene lead to the progressive inhibition of the central nervous system (CNS),

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

followed by coma, respiratory weakness, and finally absence of cerebral blood flow and death. High concentrations cause coma and respiratory weakening, destabilize the function of the kidneys and lead to liver damage. At low concentrations, irritation of the eyes, nasopharynx, illness, irritation, slow reaction times and reduced short-term memory occur. Vapors of xylene can cause dizziness, headache, nausea, mental confusion. Ingestion: In the event of ingestion of xylene, the injured person has a burning sensation and stomach ache, in case of aspiration there is a danger of chemical pneumonitis and pulmonary edema. Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Contact with eyes: Vapors of xylene and xylene in liquid form irritate the eyes and membranes.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 648 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96

Xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 73

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Duration h: 504

Endpoint: NOEC - Species: Fish = 1.3 mg/l - Duration h: 1344

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504

Endpoint: NOEC - Species: Algae > 1000 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 100 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48

Naphtha - hydrocarbons C9 aromatics - CAS: 64742-95-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.2 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2.9 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 9.2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 1 mg/l - Duration h: 72 - Notes: NOELR

Fatty acids, C14-18 and C16-18-unsatd., maleated - CAS: 85711-46-2

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

- a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Fish > 150 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72
- maleic anhydride - CAS: 108-31-6
- a) Aquatic acute toxicity:
 - Endpoint: LC50 - Species: Fish = 75 mg/l - Duration h: 96
 - Endpoint: EC50 - Species: Daphnia = 42.81 mg/l - Duration h: 48
 - Endpoint: EC50 - Species: Algae = 74.35 mg/l - Duration h: 72
- b) Aquatic chronic toxicity:
 - Endpoint: NOEC - Species: Daphnia = 10 mg/l - Duration h: 504
- 12.2. Persistence and degradability
 - Not persistent.
- 12.3. Bioaccumulative potential
 - Not bioaccumulative
- 12.4. Mobility in soil
 - Do not mix with waste water, rain or surface water. Floats on water, evaporates from liquid and solid surfaces but a significant amount may penetrate and pollute water table.
- 12.5. Results of PBT and vPvB assessment
 - vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
 - None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 - The empty containers must be considered special waste materials to take to dump of type 2B. If previously cleansed, they can be admitted in first class dumps.
 - Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. DO NOT discharge into sewers, watercourses, ponds, canals or ditches. Empty product containers must be completely drained and stored safely until appropriately processes or disposed. Empty containers must be recycled, recovered or disposed of by a qualified and authorized company operating in compliance with current recycling, recovery and disposal regulations. It is advisable to provide the desposal company with all safety information of the material contained in the empty packaging. DO NOT pressurize, DO NOT cut, DO NOT weld, DO NOT puncture, DO NOT crush, DO NOT expose empty containers to heat, flames, sparks, electrostatic discharge or other sources of ignition.

SECTION 14: Transport information



Limited quantities, not subject to ADR norms for internal packaging of up to 5 litres and maximum packaging of 30kg.

- 14.1. UN number
 - ADR-UN Number: 1263
 - IATA-UN Number: 1263
 - IMDG-UN Number: 1263
- 14.2. UN proper shipping name
 - ADR-Shipping Name: PAINT

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

IATA-Shipping Name:	PAINT
IMDG-Shipping Name:	PAINT
14.3. Transport hazard class(es)	
ADR-Class:	3
ADR-Label:	3
ADR - Hazard identification number:	30
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
IMDG-Label:	3
14.4. Packing group	
ADR-Packing Group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
14.5. Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
14.6. Special precautions for user	
ADR-Subsidiary hazards:	-
ADR-S.P.:	163 367 640E 650
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-Page:	3372
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary hazards:	-
IMDG-MFAG:	310
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
N.A.	

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) 2015/830
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
 - Regulation (EU) n. 605/2014 (ATP 6 CLP)
 - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 - Regulation (EU) n. 2016/918 (ATP 8 CLP)
 - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 - Regulation (EU) n. 2017/776 (ATP 10 CLP)
 - Regulation (EU) n. 2018/669 (ATP 11 CLP)

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Volatile Organic compounds - VOCs =255.00 g/Kg= 413.10 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.19

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H372 Causes damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EUH071 Corrosive to the respiratory tract.

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Resp. Sens. 1	3.4.1/1	Respiratory Sensitisation, Category 1
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking
 SECTION 2: Hazards identification
 SECTION 15: Regulatory information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Safety Data Sheet

F31 PLUS FILLER HS DARK GREY

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method
Skin Sens. 1A, H317	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand
Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
N.A.:	Not available
N.D.:	Not determined.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average