

Safety Data Sheet

R00 KIT-TEX P FAST



Safety Data Sheet dated 13/1/2021, version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Mixture identification:
Trade code and name: R00 KIT-TEX P FAST
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Adhesive transparent resin
Only for professional use.
- 1.3. Details of the supplier of the safety data sheet
Company:
Industria Chimica Reggiana I.C.R. Spa
(subject to management and coordination by sole shareholder company PPG Industries Inc.)
Via Gasparini, 7 42124 REGGIO EMILIA Italia
Tel. +39 0522/517803 Fax +39 0522/514384
Competent person responsible for the safety data sheet:
sdsre@icrsprint.it
- 1.4. Emergency telephone number
Tel. +39 0522-517803 or NHS 111 - dial 111

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)
 - ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
 - ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
 - ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
 - ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
 - ⚠ Warning, Repr. 2, Suspected of damaging the unborn child.
 - ⚠ Warning, STOT SE 3, May cause respiratory irritation.
 - ⚠ Danger, STOT RE 1, Causes damage to ear through prolonged or repeated exposure via inhalation..
 - Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.Adverse physicochemical, human health and environmental effects:
No other hazards
- 2.2. Label elements
Hazard pictograms:



Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H361d Suspected of damaging the unborn child.
- H335 May cause respiratory irritation.
- H372 Causes damage to ear through prolonged or repeated exposure via inhalation..
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

Safety Data Sheet

R00 KIT-TEX P FAST

P202 Do not handle until all safety precautions have been read and understood.
 P260.F Do not breathe vapours.
 P280 Wear protective gloves and eye protection.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special Provisions:

None

Contains

maleic anhydride
 styrene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 30% - < 40%	styrene	Index number: 601-026-00-0 CAS: 100-42-5 EC: 202-851-5 REACH No.: 01-2119457861-32	⚠ 2.6/3 Flam. Liq. 3 H226 4.1/C3 Aquatic Chronic 3 H412 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.7/2 Repr. 2 H361d ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.9/1 STOT RE 1 H372 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319
>= 0.25% - < 0.5%	1,1'-(p-tolyimino) dipropan-2-ol	CAS: 38668-48-3 EC: 254-075-1 REACH No.: 01-2119980937-17	⚠ 3.1/2/Oral Acute Tox. 2 H300 ⚠ 3.3/2 Eye Irrit. 2 H319 4.1/C3 Aquatic Chronic 3 H412
>= 0.25% - < 0.5%	ethanol	Index number: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 REACH No.: 01-2119457610-43	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319
>= 0.1% - < 0.25%	Propan-2-ol	Index number: 603-003-00-0 CAS: 67-63-0 EC: 200-661-7 REACH No.: 01-2119457558-25	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H336

Safety Data Sheet

R00 KIT-TEX P FAST

>= 0.01% - < 0.1%	maleic anhydride	Index number: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 REACH No.: 01-2119472428-31	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.9/1 STOT RE 1 H372 ⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.1/1 Resp. Sens. 1 H334 ⚠ 3.4.2/1A Skin Sens. 1A H317 EUH071
----------------------	------------------	---	---

This product is not classified H304 due to its high viscosity.

All component substances of this product have been registered under REACH or are exempt from REACH registration.

Substances in Section 3 not showing REACH registration codes are exempt from registration.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. If irritation persists: Get medical advice/attention.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for at least 15 minutes, then consult a medic immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Ventilate the premises. The patient is to be removed immediately from the contaminated premises to rest in a well ventilated area. OBTAIN MEDICAL ATTENTION.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

See section 11 for known symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Do not use water jets. Water may not be effective fire fighting measure, however it can be used to cool closed

containers close to flames as to avoid bursting and exploding.

None in particular.

Safety Data Sheet

R00 KIT-TEX P FAST

- 5.2. Special hazards arising from the substance or mixture
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke. Carbon oxides.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 - Provide adequate ventilation.
 - Use appropriate respiratory protection.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Exercise the greatest care when handling or opening the container.
 - Use localized ventilation system.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - See also section 8 for recommended protective equipment.
 - Advice on general occupational hygiene:
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Always keep in a well ventilated place.
 - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 - Keep away from food, drink and feed.
 - None in particular.
 - Instructions as regards storage premises:
 - Cool and adequately ventilated.
- 7.3. Specific end use(s)
 - See Point 1.2.

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - styrene - CAS: 100-42-5

Safety Data Sheet

R00 KIT-TEX P FAST

EU - TWA(8h): 85 mg/m³, 20 ppm - STEL(): 170 mg/m³, 40 ppm - Notes: Pelle
ACGIH - TWA(8h): 10 ppm - STEL: 20 ppm - Notes: OTO, A3, BEI - CNS and hearing
impair, URT irr, peripheral neuropathy, visual disorders
Italy - TWA(8h): 20 ppm - STEL: 200 ppm

ethanol - CAS: 64-17-5
EU - TWA: 1000 ppm
ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr

Propan-2-ol - CAS: 67-63-0
ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS
impair
EU - TWA(8h): 492 mg/m³, 200 ppm - STEL: 983 mg/m³, 400 ppm

maleic anhydride - CAS: 108-31-6
ACGIH - TWA(8h): 0.01 mg/m³ - Notes: (IFV), DSEN, RSEN, A4 - Resp sens

DNEL Exposure Limit Values
styrene - CAS: 100-42-5
Worker Professional: 406 mg/kg - Consumer: 343 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
Consumer: 2.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Professional: 85 mg/m³ - Consumer: 10.2 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects
Worker Professional: 289 mg/m³ - Consumer: 174.25 mg/m³ - Exposure: Human Inhalation -
Frequency: Short Term, systemic effects
Worker Professional: 306 mg/m³ - Consumer: 182.75 mg/m³ - Exposure: Human Inhalation -
Frequency: Short Term, local effects

1,1'-(p-tolylimino)dipropan-2-ol - CAS: 38668-48-3
Worker Industry: 2 mg/m³ - Worker Professional: 2 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects
Worker Industry: 0.6 mg/kg - Worker Professional: 0.6 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects

ethanol - CAS: 64-17-5
Worker Professional: 1900 mg/m³ - Consumer: 950 mg/m³ - Exposure: Human Inhalation -
Frequency: Short Term, local effects
Worker Professional: 343 mg/kg - Consumer: 206 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
Worker Professional: 950 mg/m³ - Consumer: 114 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects
Consumer: 87 04 - Exposure: Human Oral - Frequency: Long Term, systemic effects

Propan-2-ol - CAS: 67-63-0
Worker Professional: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
Worker Professional: 500 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term,
systemic effects
Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects -
Notes: bw/day

PNEC Exposure Limit Values
styrene - CAS: 100-42-5
Target: Fresh Water - Value: 0.028 mg/l
Target: Marine water - Value: 0.028 mg/l
Target: Freshwater sediments - Value: 0.614 mg/kg
Target: Marine water sediments - Value: 0.0614 mg/kg
Target: Soil (agricultural) - Value: 0.2 mg/kg
Target: 14 - Value: 0.04 mg/l
Target: Purification plant - Value: 5 mg/l

1,1'-(p-tolylimino)dipropan-2-ol - CAS: 38668-48-3

Safety Data Sheet

R00 KIT-TEX P FAST

Target: Microorganisms in sewage treatments - Value: 199.5 mg/l

Target: Marine water - Value: 0.00782 mg/kg

Target: Fresh Water - Value: 0.017 mg/l

ethanol - CAS: 64-17-5

Target: Marine water - Value: 0.79 mg/l

Target: Intermittent emissions - Value: 2.75 mg/l

Target: Purification plant - Value: 580 mg/l

Target: Freshwater sediments - Value: 3.6 mg/kg

Target: Marine water sediments - Value: 2.9 mg/kg

Target: Soil - Value: 0.63 mg/kg

Target: Oral - Value: 0.72 g/kg

Target: Fresh Water - Value: 0.96 mg/l

Propan-2-ol - CAS: 67-63-0

Target: STP - Value: 2251 mg/l

Target: Intermittent emissions - Value: 140.9 mg/l

Target: Freshwater sediments - Value: 552 mg/kg

Target: Marine water sediments - Value: 552 mg/kg

Target: Soil - Value: 28 mg/kg

Target: Oral - Value: 160 mg/kg

Target: Fresh Water - Value: 140.9 mg/l

Target: Marine water - Value: 140.9 mg/l

Biological Exposure Index

styrene - CAS: 100-42-5

Value: 400 mg/g creatinine - medium: Urine - Biological Indicator: Mandelic acid in urine and fenilgliosilico - Sampling Period: End of turn

Value: 40 mg/l creatinine - medium: Urine - Biological Indicator: Styrene in urine - Sampling Period: End of turn

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles and/or visor conforming to BS 2092 GRADE 1).

Protection for skin:

Wear safety clothing that ensure full skin protection in accordance to EN 14605 Type 4 in case of spills or spray (e.g. Tyrek). Please note: safety clothing must be changed immediately if it comes in contact with product.

Protection for hands:

Use protective gloves that provides comprehensive protection, EN374 Class 3 (F). Permeation time > 60 minutes; 0.4 mm thickness.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory devices, using Filter "A" (Brown colour) for organic gas and vapors with boiling points over 65°C.

Thermal Hazards:

None

Environmental exposure controls:

Emissions from ventilation systems or from work processes must be check as to ensure compliance to environmental protection legislation. In some cases the addition of vapour scrubbers, filters or other system modification may be necessary in order to reduce emissions to acceptable levels.

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Safety Data Sheet

R00 KIT-TEX P FAST

Properties	Value	Method:	Notes
Appearance and colour:	Light-yellow transparent liquid	--	--
Odour:	Typical of Styrene	--	--
Odour threshold:	-31°C	--	--
pH:	N.A.		
Melting point / freezing point:	N.D.	--	--
Initial boiling point and boiling range:	145 °C	--	--
Flash point:	32 °C	--	--
Evaporation rate:	N.D.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.D.	--	--
Vapour pressure:	6,7 hPa	--	--
Vapour density:	3.6 (air=1)	--	--
Relative density:	1.116 g/cm ³	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.D.	--	--
Partition coefficient (n-octanol/water):		--	--
Auto-ignition temperature:	490°C	--	--
Decomposition temperature:	N.D.	--	--
Viscosity:	> 20.5 mm ² (40°C)	--	--
Explosive properties:	N.D.	--	--
Oxidizing properties:	N.D.	--	--

9.2. Other information

Safety Data Sheet

R00 KIT-TEX P FAST

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under recommended use and storage conditions (see point 7).

10.3. Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid accumulating electrostatic charge.

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

Carbon oxides. Aromatic hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

styrene - CAS: 100-42-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 11.8 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Notes: OECD 402

i) STOT-repeated exposure:

Test: LOAEL(C) - Route: Oral - Species: Rat = 2000 mg/kg - Notes: bw/day

Test: NOAEL(C) - Route: Oral - Species: Rat = 1000 mg/kg - Notes: bw/day

Test: LOAEL(C) - Route: Inhalation - Species: Rat = 0.21 mg/l

1,1'-(p-tolylimino)dipropan-2-ol - CAS: 38668-48-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 25 mg/kg

Test: LD50 - Route: Skin - Species: GUINEA PIG > 2000 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rabbit Positive

c) serious eye damage/irritation:

Test: Eye Corrosive - Species: Rabbit Positive

ethanol - CAS: 64-17-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 21 g/kg

Safety Data Sheet

R00 KIT-TEX P FAST

Test: LD50 - Route: Oral - Species: Rabbit = 6300 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 20 g/kg

Propan-2-ol - CAS: 67-63-0

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit = 12800 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 5000 mg/kg

styrene - CAS: 100-42-5

Symptoms may appear many hours after exposure. Medical observation is therefore necessary for 48 hours after exposure. May cause sleepiness or dizziness. Inhalation: may irritate respiratory tract. Ingestion: may irritate gastrointestinal tract, along with nausea, vomit and diarrhea, disorientation. Inhalation, skin contact or ingestion may result in reduced fetal weight, increase risk of fetal death, skeletal malformations.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

styrene - CAS: 100-42-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 4.02 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 4.9 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 4.7 mg/kg - Duration h: 48

Endpoint: EC10 - Species: Algae = 0.28 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 1.01 mg/l - Duration h: 504

12.2. Persistence and degradability

Not persistent.

12.3. Bioaccumulative potential

Not bioaccumulative

12.4. Mobility in soil

Do not mix with waste water, rain or surface water. Floats on water, evaporates from liquid and solid surfaces but a significant amount may penetrate and pollute water table.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The empty containers must be considered special waste materials to take to dump of type 2B. If

Safety Data Sheet

R00 KIT-TEX P FAST

previously cleansed, they can be admitted in first class dumps.
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. DO NOT discharge into sewers, watercourses, ponds, canals or ditches. Empty product containers must be completely drained and stored safely until appropriately processes or disposed. Empty containers must be recycled, recovered or disposed of by a qualified and authorized company operating in compliance with current recycling, recovery and disposal regulations. It is advisable to provide the desposal company with all safety information of the material contained in the empty packaging. DO NOT pressurize, DO NOT cut, DO NOT weld, DO NOT puncture, DO NOT crush, DO NOT expose empty containers to heat, flames, sparks, electrostatic discharge or other sources of ignition.

SECTION 14: Transport information

ADR/RID-Class

If transported without hardener:

Not liable for receptacles equal or less than 450 litres, transported in accordance with 2.2.3.1.5 ADR.

If transported as Polyester Resin Kit (with hardener):

Limited quantities, not liable to ADR norms for internal packages of up to 5L and a maximum 30 kg per pack.

UN number:	3269
Packing Group:	III
Shipping Name:	Polyester Resin Kit
Transport category :	3
Classification code:	F1
Label:	3

IMDG/IMO

If transported without hardener:

UN number:	1263
Packing Group:	III
Shipping Name:	Paint
Transport category :	3
Class:	3
IMDG-label:	3
IMDG-EMS:	F-E,S-E

If transported as Polyester Resin Kit (with hardener):

UN number:	3269
Packing Group:	III
Shipping Name::	Polyester Resin Kit
Transport category:	3
Class:	3
IMDG-label:	3
IMDG-EMS:	F-E,S-D

Marine pollutant MARPOL (Annex II/III): No

For the correct trasport classification according to European decrees pertaining to international transport of dangerous goods by road (ADR) and by sea (IMDG), please refer to the goods' transport documentation.

Safety Data Sheet

R00 KIT-TEX P FAST

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
Restriction 40

Restrictions related to the substances contained:

No restriction.

Volatile Organic compounds - VOCs = 370.00 g/Kg = 412.92 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.32

Dry weight (% wt): 63

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1
Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H332 Harmful if inhaled.

Safety Data Sheet

R00 KIT-TEX P FAST

H372 Causes damage to ear through prolonged or repeated exposure via inhalation..
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H300 Fatal if swallowed.
 H225 Highly flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 H302 Harmful if swallowed.
 H372 Causes damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 EUH071 Corrosive to the respiratory tract.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 2	3.1/2/Oral	Acute toxicity (oral), Category 2
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Resp. Sens. 1	3.4.1/1	Respiratory Sensitisation, Category 1
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

Safety Data Sheet

R00 KIT-TEX P FAST

SECTION 2: Hazards identification
SECTION 3: Composition/information on ingredients
SECTION 7: Handling and storage
SECTION 8: Exposure controls/personal protection
SECTION 9: Physical and chemical properties
SECTION 10: Stability and reactivity
SECTION 11: Toxicological information
SECTION 15: Regulatory information
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1A, H317	Calculation method
Repr. 2, H361d	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.
Exposure scenario available upon request.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand
Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.

Safety Data Sheet

R00 KIT-TEX P FAST

EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
N.A.:	Not available
N.D.:	Not determined.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average