



A11 SPOT PRIMER

1K ANTI-CORROSIVE ANCHORING PRIMER

High adhesion Anti-corrosive, 1k acrylic primer for body shop repair cycles. The product features rapid drying time, good protection against corrosion and excellent adhesion to supports, such as bare metal, aluminium and galvanised metal sheet.

The EU limit for this product (product category IIB.e) is 840 g/l. The VOC of this product is below 840 g/l

B) TECHNICAL DATA:

| | |
|-------------------|--|
| Composition | Acrylic resins, mineral fillers and solvents |
| Specific weight | 1,26 ± 0,1 |
| Available colours | Dark grey |
| Safety data | Refer to the safety sheet |

C) SURFACE PREPARATION :



*Sheet metal, sheet aluminium, polyester laminates, wood, polyester fillers, etc.

*Old top coats, including those in thermoplastic acrylic and double layers.



*Dry sand with P180-P220 paper.

*Clean the surface to be treated thoroughly with Antisol V09 and ensure it is dry with no traces of silicon, wax, grease or foreign matters in general

D) CAUTIONS:

- * Comply with the specified drying times between one coat and the next.
- * Do not use the product at temperatures below 5°C.
- * Keep in a cool, dry place.



A11 SPOT PRIMER

sheet #

A11

E) PROCESSING:



2 coats = 15-25 micron



15-30 minutes at 20°C.



P600-P1000

F) TOOLS CLEANING:

* With nitro solvent.

G) RECOATING :

2k Acrylic and polyurethane top coat
Basecoat water and solvent based

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained